

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
29 June 2006 (29.06.2006)

PCT

(10) International Publication Number
WO 2006/067581 A1

(51) International Patent Classification:

F02D 13/02 (2006.01) F02D 35/02 (2006.01)
F02D 41/40 (2006.01) F02D 35/00 (2006.01)

(21) International Application Number:

PCT/IB2005/003800

(22) International Filing Date:

16 December 2005 (16.12.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2004-367969 20 December 2004 (20.12.2004) JP

(71) Applicant (for all designated States except US): TOYOTA JIDOSHA KABUSHIKI KAISHA [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): IDOGAWA, Masanao [JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA, 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571


(JP). HOSOKAWA, Osamu [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: VALVE CHARACTERISTIC CONTROL APPARATUS FOR INTERNAL COMBUSTION ENGINE



(57) Abstract: A valve characteristic control apparatus is provided in an internal combustion engine including a variable valve mechanism that can change at the least, among valve characteristics of an exhaust valve, a closing timing of the exhaust valve, and in which a number of injections of fuel is changed during one engine cycle. The valve characteristic control apparatus sets the closing timing of the exhaust valve to a retard side during an engine warming up operation. When setting to the retard side is performed, if two injections are performed, an exhaust side target displacement angle VTT_{ex} of the exhaust valve is calculated based on a dual injection use map. On the other hand, if one injection is performed, the exhaust side target displacement angle VTT_{ex} of the exhaust valve is calculated based on a single injection use map.



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.